



FX FIRE BALL TECHNICAL DETAILS

Weight: 1.3 Kg +/- 20 gms

Size: 144 mm Diameter

Automated operation: 60-80 degrees (flame)
220-285 (Atmospheric Temperature)

Covers: wide area 360 degree angle (One ball is enough for a 10 X 10 Room)

Sound: within 125-138 decibels

Activation Time: 3-8 Seconds

Maintenance: 5 years -No maintenance

Contents: Mono Amonium Phosphate (94.94%)

Apparant Density: 1.175

Hygroscopy:1.27%

Water Reppellency: 0.83%

Material Type: Eco Friendly - Bio Degradable

Product Life: 5 years

Fire class:Solid, Liquid, Electrical

Areas: One ball is to enough to cover
2.596 Cubic Mtrs

Usage: Manual / Automatic

Fuses: Fuses available at 4 sides

Training: No Training Required

Mal-functioning Rate: Zero

Activation Method : Open fire

Installation Time: Minimum

Extinguish Effect: Moist /Dry/Clean

Mobility: Mobile

Health: Harmless

Fitment: Can be fitted anywhere

Usage Distance: Safe distance

Method of action: Cooling, Cutting,Oxygen

Damage to Electric Device:Low

Chemical Content: 1.3 Kg +/- 20 gms

Fire class that covers: Solid,Liquid & Gas

Resistance to compression: Without crack for 5 Kg for 1 hr

Drop Test: No damage for 2.5 Meters from cement floor

Certifications from: National Test House, Kolkata,Fire Test & Research, Delhi, Dept of Industries, Andhra Pradesh

